

# N65KD CE-172M CHECKLIST

## NORMAL TAKEOFF

1. Flaps.....UP
2. Carb Heat.....OFF
3. Throttle.....FULL
4. Elevator Control.....LIFT NOSE WHEEL (60 MPH)
5. Climb Speed.....75-80 MPH

## ENROUTE CLIMB

1. Airspeed.....80-90 MPH
2. Mixture.....LEAN AS REQUIRED

## CRUISE

1. Mixture.....LEAN AS REQUIRED
2. Engine Instruments.....CHECK

## DESCENT

1. Fuel Selector Valve.....BOTH
2. Mixture.....AS REQUIRED

## BEFORE LANDING

1. Fuel Selector Valve.....BOTH
2. Mixture.....RICH
3. Carb Heat.....ON
4. Seat Belts.....ON

## NORMAL LANDING

1. Flaps.....AS DESIRED
2. Airspeed.....FLAPS DOWN 65-75 MPH

## AFTER LANDING

1. Flaps.....UP
2. Carb Heat.....OFF
3. Mixture.....1/2in LEAN FOR TAXI

## SHUTDOWN

1. Avionics Master.....OFF
2. Electrical Switches.....OFF
3. Throttle.....~1000 RPM
4. Mixture.....IDLE CUTOFF
5. Magnetos.....OFF
6. Master Switch.....OFF
7. Control Lock.....INSTALL
8. Tie Downs.....SECURE
9. Post Flight Inspection.....COMPLETE

## BEFORE START

1. Passenger Safety Brief.....COMPLETE
2. Seat Belts.....ON
3. Fuel Selector Valve.....BOTH
4. Radios and Electrical Equipment.....OFF
5. Circuit Breakers.....CHECKED

## ENGINE START

1. Rotating Beacon.....ON
2. Mixture.....RICH
3. Throttle.....1/8" OPEN
4. Carb Heat.....OFF
5. Brakes.....SET
6. Master Switch.....ON
7. Primer.....AS NEEDED
8. Prop Area.....CLEAR
9. Ignition Switch.....START
10. Throttle.....800 RPM
11. Oil Pressure.....CHECK

## AFTER START

1. Flaps.....UP
2. Avionics Master.....ON
3. Mixture.....1/2in LEAN FOR TAXI
4. Taxi Light.....ON
5. ATIS.....COPY

## TAXI

1. Doors.....LOCKED
2. Area.....CLEAR
3. Yoke.....AFT FOR TAXI
4. Brakes.....CHECK

## BEFORE TAKEOFF CHECK

1. Nose Wheel.....STRAIGHT
2. Flight Controls.....FREE AND CORRECT
3. Fuel Selector Valve.....BOTH
4. Trim.....SET FOR TAKEOFF
5. Mixture.....RICH
6. Throttle.....1700 RPM
  - a. Mag Check.....125 RPM MAX - 50 DIF
  - b. Carb Heat.....CHECK DROP
  - c. Engine Instruments.....CHECK
  - d. Ammeter.....CHECK
7. Throttle.....IDLE CHECK / THEN 800 - 1000 RPM
8. Flight Instruments/G5.....SET
9. Radios.....SET
10. Lights.....ON
11. Time.....NOTED

## EMERGENCY PROCEDURES

### ENGINE FAILURE

1. Best Glide - 75 MPH
2. Fuel ON.
3. Mixture RICH.
4. Throttle OPEN.
5. Carb Heat ON.
6. Ignition Switch ON
7. Primer IN and LOCKED

### FORCED LANDING

1. Airspeed - 75 MPH Flaps UP,  
70 MPH Flaps DOWN
2. Fuel Valve OFF
3. Mixture IDLE CUTOFF
4. Ignition Switch OFF
5. Radios/Flaps AS REQUIRED
6. Master Switch OFF
7. Seatbelts TIGHTEN
8. Doors UNLATCHED
9. Touchdown SLIGHTLY TAIL LOW

### ELECTRICAL FIRE INFLIGHT

1. Master Switch OFF
2. All Switches OFF (except ignition).
3. Vents and Windows CLOSED.
4. Use Extinguisher if Needed.
5. Master Switch ON.
6. Circuit Breakers CHECK
7. Radios/Electrical Switches ON one at a time
8. Vents and Windows OPEN when fire is out

### ENGINE FIRE IN FLIGHT

1. Mixture IDLE CUTOFF
2. Fuel Shutoff Valve OFF
3. Master Switch OFF
4. Cabin Air/Heat OFF
5. Airspeed >100MPH
6. Forced Landing EXECUTE

### FREQUENCIES

#### Twin Oaks

CTAF 123.05  
Portland App 118.1/126.0  
Clearance 119.95

#### McMinnville

CTAF 123.00  
ASOS 135.67

#### Hillsboro

Tower 119.3  
ATIS 127.65  
Ground 121.7

#### Aurora

Tower 120.35  
ATIS 118.52  
GROUND 119.15

**West Practice Area 122.75**

## N65KD CE-172M

Speeds	
<b>V<sub>SO</sub> Stall in Landing Config.</b>	<b>49</b>
<b>V<sub>S</sub> Stall Clean</b>	<b>57</b>
<b>V<sub>X</sub> Best Angle</b>	<b>68</b>
<b>V<sub>Y</sub> Best Rate</b>	<b>91 (sea level) 80 (at 10,000')</b>
<b>V<sub>REF</sub> Flaps Up</b>	<b>70-80</b>
<b>V<sub>REF</sub> Flaps Down</b>	<b>65-75</b>
<b>V<sub>FE</sub> Flaps Extended</b>	<b>100</b>
<b>V<sub>A</sub> Maneuvering Speed</b>	<b>112</b>
<b>V<sub>NO</sub> Max Structural Cruise</b>	<b>145</b>
<b>V<sub>NE</sub> Never Exceed</b>	<b>182</b>
<b>V<sub>G</sub> Best Glide</b>	<b>75 (flaps up) 70 (flaps down)</b>
Short Field Takeoff (Flaps Up)	<b>68 (no flaps)</b>
Short Field Approach	<b>70 (40° flaps)</b>

**NOTE:** Avoid slips with full flaps; it may cause the elevator to oscillate.

Fuel	
<b>Total Capacity</b>	42 US GAL
<b>Usable</b>	38 US GAL
Engine	
<b>Horsepower</b>	160 at 2700 RPM
<b>Oil Capacity (minimum)</b>	8 quarts (6 min)
<b>Fuel Burn at 75% power at 5000ft</b>	8.1 GPH
Weight	
<b>Max Gross Weight</b>	2300 lbs

All information taken from the respective owner's manuals and supplemental data.  
This is for reference only and NOT to be used for flight planning.

## N65KD CE-172M